



CHASSIS

Tata / Ashok Leyland / MAN / Volvo Mercedes Benz / Eicher / Swaraj Mazda From 6 tons - 25 Tons GVW are available With OEM manufactured cabin or cowl

VEHICLE DESIGN

Modularly built for ease of accessibility Built as per latest International designs

DRIVER / CREW CABIN

Two door or Four door extendo-cabs 1 Driver, 1 officer & 4/5 crew members Seats with Breathing Apparatus in-built OEM or customized cabins are available

DCP SYSTEM:

1 or 2 vessels of Dry Chemical Powder Starting from 500 kgs. up to 4000 kgs Safety valve is normally set at 16kg/cm² Working pressure of 14kg/cm² standard System mounted behind the driver cabin

DCP MONITOR

Capacity Up to 40 kg / sec @ 14kg/cm2 Positions settings of 15kg, 25kg & 40kg 40m horizontal powder throw in still air On roof immediately behind driver cabin

DCP HOSE REELS

1 to 4 hose reels depending on the capacity Discharge from the DCP gun 5kg @ 14 Bar 30 Mtr. hose length & trigger type DCP gun 10 Mtrs. min. horizontal throw in still air

NITROGEN CYLINDER

Cylinders from 50-80ltrs capacity available Filling pressures up to 200 Kg/cm²

CONTROL PANEL

Well illuminated control panel provided All gauges & valves ergonomically grouped N2 charging / Monitor valve placed nearby External Flushing valve fitted as standard

LOCKERS WITH ROLLER SHUTTERS

Indigenous/ Imported roller shutters Swing down floor boards for standing Guide rail shutter supports on both sides Sturdy lock prevents accidental opening Watertight, weather/corrosion resistant

ELECTRICAL FITTINGS

Fog lights / spot-lights on roof standard Various combinations of Strobe Bar Lights L E D Illumination for lockers & shutters Searchlight for night time operations

OPTIONAL WINCH

Hydraulic or Electrical (12 / 24 Volts) Cable or remote controlled operation Capacities from 2 to 10 tons are available Cable lengths from 15-40 Mtrs available

OPTIONAL UHP PUMP

Ultra High Pressure Positive Displacement Scratch proof ceramic plungers / cylinders 40 LPM upto 150 LPM @ 100 bar pressure Foam mixer - 0-3% provided as standard Pump directly connected to the hose reels Safety features as per latest Intl. standards Directly coupled to PTO or engine driven Lancing distance of up to 30 Mtrs possible

OPTIONAL ACCESSORIES & EQUIPMENT

Details of all other optional accessories and equipments which can be fitted on an DCP tenders are available on request. Please contact us on the below mentioned contact details and we will be happy help t o y o u

lıladia Group

Nr. Dinbai Tower, Mirzapur Road, Ahmedabad-380 001, India.

Phone +91-79-25506040 Fax: +91-79-25506159

Web www.wadiafire.in

e-mail wadiaoffice@gmail.com