



CHASSIS

Tata / Ashok Leyland / MAN / Volvo Mercedes Benz / Eicher / Swaraj Mazda From 6 tons - 25 Tons GVW are available With OEM manufactured cabin or cowl

MONITOR

Manual as well as fully remote controlled From 4000 LPM to 8000 LPM available Throw up to 85 Mtrs. @10 Bar available SS / Bronze & Aluminum construction

ELECTRICAL FITTINGS

Fog lights / spotlights on roof standard Combinations of various Strobe Bar Lights L E D illumination for lockers & shutters Search Light for night time operations

VEHICLE DESIGN

Modularly built for ease of accessibility Shutters / drawers for equipment / slides Built as per latest International designs

PTO

Chassis OEM PTO's are standard fitment Imported side PTO's available as optional Ratio of PTO's depending on pump capacity

OPTIONAL UHP PUMP

Ultra High Pressure Positive Displacement Scratch proof ceramic plungers / cylinders 40 LPM upto 150 LPM @ 100 bar pressure Foam mixer - 0-3% provided as standard Pump directly connected to the hose reels Safety features as per latest Intl. standards Directly coupled to PTO or engine driven Lancing distance of up to 30 Mtrs possible

DRIVER / CREW CABIN

Two door or Four door extended cabins 1 Driver, 1 officer extendo-cabs 4/5 crew members Seats with Breathing Apparatus in-built OEM or customized cabins are available

CONTROL PANEL

Well illuminated control panel provided All gauges are ergonomically grouped LED / Tube Level gauges for tanks Auxiliary throttle control for the Engine

OTHER OPTIONAL EQUIPMENT

Details of all other optional accessories and equipments which can be fitted on a Foam Nusers are available on request. Please contact us on the below mentioned contact details and we will be happy to help you

FOAM TANK :

From 2000 Ltrs. to 18000 Ltrs available From 3mm to 6mm SS sheets for tank

LOCKERS WITH ROLLER SHUTTERS

Indigenous/ Imported roller shutters Roll In-Roll Out drawers on bearings Aluminum Extrusions extensively used Swing down floor boards for standing Guide rail shutter supports on both sides Sturdy lock prevents accidental opening Watertight, weather/corrosion resistant

FOAM PUMP:

Rotary type from 500 LPM to 1000 LPM Casing materials Bronze or SS 316 Stainless Steel Shaft of different grades Mechanical Carbon Seal / Gland Sealing

- Automatic Transmission System
- Integrated Control Panel
- Ladder Gantry
- Electrical Hose Reel
- Extended Cabin